

# MK6-03X

Keystone Jack Cat6 - 50µ gold - Unshielded



Where **X** = Color

X = I = Ivory      X = W = White      X = K = Black  
X = O = Orange    X = B = Blue      X = R = Red

(Other Colors Upon Request)

## Features:

Materials	
Jack Housing	ABS+PC, UL94V-0
Jack Contact Bracket	PBT + Glass Fiber, UL 94V-0
Jack Contact	Phosphor Bronze with Nickel Plating
Jack Contact Finish	50 micro-inch Gold Plated on Plug Contact Area
IDC Housing	PC + Glass Fiber
IDC Terminal	Phosphor Bronze with Tin Plating
IDC Cap	PC 1250Y UL 94V-B
IDC Brackets	ABS
PCB	FR4
Technical Information	
Wiring	T568A & T568B
Compliance	ANSI/TIA 568 C.2
Performance	
Insertion Force	20N Max
Retention Strength	7.7kg between Jack and Plug
Operating Temperature	-10°C to 60°C
Mating Cycles	Jack 750 Cycles Minimum
	IDC: Suitable for 23-26 AWG Stranded and Solid Wire, Compatible with 110 Punch Down Tools

# MK6-03X

Keystone Jack Cat6 - 50μ gold - Unshielded



## Diagram:

