

MKE-01X

Keystone Jack Cat5e 90°, 50 u gold , Unshielded



MKE-01X is a Cat5e unshielded keystone jack where the X = Color:

X=I = Ivory X=O = Orange X=W = White
X=B = Blue X=K = Black X=R = Red

Features:

Material	
RJ45 Jack Housing	ABS+PC, UL94V-0
RJ45 Jack Bracket Set	PBT + Glass Fiber, UL 94V-0
RJ45 Contact	Phosphor Bronze with Nickel Plating
Finish	50 micro-inch Gold Plated on Plug Contact Area
IDC 3.1 Housing	PC + Glass Fiber
Terminal	Phosphor Bronze with Tin Plated
IDC Cap	ABS, UL 94V-HB
IDC Bracket	ABS, UL 94V-0
PCB	FR4, UL 94V-0
Technical Information	
Wiring	T568A & T568B
Compliance	Transmission Performance in compliance with the ANSI/TIA 568 C.2 Standard
Performance	
Insertion Force	20N max
Retention Strength	7.7kg Between Jack and Plug
Operating Temperature	-10°C to 60°C
Life (Mating cycles)	Jack: 750 cycles min.
	IDC: suitable for 22-226 AWG Stranded and Solid Wire. Compatible with both 110 & Krone punch down tools

MKE-01X

Keystone Jack Cat5e 90°, 50 u gold , Unshielded



Diagram:

