

MPE-11X

Patch Panel Cat5e, 48 Ports – 2U X 19"



Where X = Color

X = W = White X = K = Black

Features:

Materials	
Panel	SPCC, 1.5mm Thickness
RJ45 Jack Housing	ABS, UL 94V-0
RJ45 Jack Contact Bracket	PC, UL 94V-2
RJ45 Jack Contact	Phosphor Bronze with Nickel Plating
RJ45 Jack Contact Finish	50 micro-inch Gold Plated on Plug Contact Area
IDC Housing	PC + Glass Fiber, UL 94V-2
IDC Terminal	Phosphor Bronze with Tin Plating
Jack Bracket Set	ABS, UL 94V-0
Panel Bracket	ABS, UL 94V-0
PCB	FR4, UL 94V-0
Performance	
Wiring	T568A & T568B
Insertion Force	20N Max
Retention Strength	7.7kg Between Jack and Plug
Operation Temperature	-10C to 60C
Jack Life (Mating Cycles)	750 Cycles Min
IDC Life (Mating Cycles)	Suitable for 22-26 AWG Stranded and Solid Wire, Compatible with both 110 & Krone Punch Down Tools
Compliance	The Cat5e transmission performance follows the ANSI/TIA/EIA 568 B.2 Standard

MPE-11X

Patch Panel Cat5e, 48 Ports – 2U X 19"



Diagram:

