


# OT9-APC

Optic Fiber Pigtail Simplex 0.9 mm



Ordering Information			
	Code	Description	Length
SC	OT9-06 15A	Pigtail Fiber 09/125 SC/APC Simplex 1.5M/0,9 mm	1.5 Mts
	OT9-06 30A	Pigtail Fiber 09/125 SC/APC Simplex 3.0M/0,9 mm	3 Mts
LC	OT9-11 15A	Pigtail Fiber 09/125 LC/APC Simplex 1.5M/0,9 mm	1.5 Mts
	OT9-11 30A	Pigtail Fiber 09/125 LC/APC Simplex 3.0M/0,9 mm	3 Mts

## Features:

Specification	
Fiber Type	SM G657
Jacket Materials	PVC
Connector Type	SC/LC
Ferrule Materials	CERAMIC
Testing Wavelengths	1310+-30/1550+-30NM
Insertion Loss (dB) TIA/EIA-455-117	<0.3dB (PC/UPCV/APC)
Return Loss (dB) TIA/EIA-455-117	>45dB (PC/UPC) >55dB (APC)
Exchangeable	<0.2dB
Operating Temperature	-10° to 70°
Storage Temperature	-40° to 85°

## Applications:

FTTH access network / Telecommunication Networks / CATV Networks / Data communications Networks / Local Area Networks