OFT-PGG XXX

Preformed Guy end Grip Galvanized Steel





The OFT-PGG XXX preforms are made up of 5 powerful helical ASTM A36 steel wires to evenly distribute the gripping force and tension, their anti-corrosion process is based on the ASTM 123 hot-dip galvanized standard. The OFT-PGGXX is designed for the perfect anchoring of ADSS cables in the deployment of FTTX networks.

Features:

5 Wires – 100 Meters				
From	Up to	Wires	Length	Unit
8.6	9.6	5 x 2.5mm	700	millimeter
8.0	9.0	5 x 2.5mm	700	millimeter
9.6	10.6	5 x 2.5mm	700	millimeter
10.6	11.6	5 x 2.5mm	700	millimeter
11.1	12	5 x 2.5mm	700	millimeter
12.1	13	5 x 2.5mm	700	millimeter
13.1	14	5 x 2.5mm	700	millimeter
14.1	15	5 x 2.5mm	700	millimeter
5 Wires – 150 Meters				
From	Up to	Wires	Length	Unit
8.6	9.6	5 x 2.5mm	900	millimeter
9.6	10.6	5 x 2.5mm	900	millimeter
10.6	11.6	5 x 2.5mm	900	millimeter
11.1	12	5 x 2.5mm	900	millimeter
11.6	12.8	5 x 2.5mm	900	millimeter
12.1	13	5 x 2.5mm	900	millimeter
13.1	14	5 x 2.5mm	900	millimeter
14.1	15	5 x 2.5mm	900	millimeter
	8.6 8.0 9.6 10.6 11.1 12.1 13.1 14.1 5 From 8.6 9.6 10.6 11.1 11.6 12.1 13.1	From Up to 8.6 9.6 8.0 9.0 9.6 10.6 10.6 11.6 11.1 12 12.1 13 13.1 14 14.1 15 5 Wires - 1 5 Wires - 1 From Up to 8.6 9.6 9.6 10.6 11.1 12 11.6 12.8 12.1 13 13.1 14	From Up to Wires 8.6 9.6 5 x 2.5mm 8.0 9.0 5 x 2.5mm 9.6 10.6 5 x 2.5mm 10.6 11.6 5 x 2.5mm 11.1 12 5 x 2.5mm 12.1 13 5 x 2.5mm 13.1 14 5 x 2.5mm 14.1 15 5 x 2.5mm 5 Wires - 150 Meters From Up to Wires 8.6 9.6 5 x 2.5mm 9.6 10.6 5 x 2.5mm 10.6 11.6 5 x 2.5mm 11.1 12 5 x 2.5mm 11.6 12.8 5 x 2.5mm 12.1 13 5 x 2.5mm 13.1 14 5 x 2.5mm	From Up to Wires Length 8.6 9.6 5 x 2.5mm 700 8.0 9.0 5 x 2.5mm 700 9.6 10.6 5 x 2.5mm 700 10.6 11.6 5 x 2.5mm 700 11.1 12 5 x 2.5mm 700 12.1 13 5 x 2.5mm 700 13.1 14 5 x 2.5mm 700 14.1 15 5 x 2.5mm 700 5 Wires - 150 Meters From Up to Wires Length 8.6 9.6 5 x 2.5mm 900 9.6 10.6 5 x 2.5mm 900 10.6 11.6 5 x 2.5mm 900 11.1 12 5 x 2.5mm 900 11.6 12.8 5 x 2.5mm 900 12.1 13 5 x 2.5mm 900 13.1 14 5 x 2.5mm 900