

# OFT-DCA NA

Dead End Clamp Hardware Type A Without Arms



The fittings retain a symmetrical structure, without imperfections, wrinkles, or cracks, throughout its structure, length and welding points.

## Features:

Specifications	
<b>SPAN</b>	Minimum span 200 meters
<b>Pole clamping mode</b>	with 3/4 "stainless steel or strapping tape
<b>Fitting base dimensions</b>	50 mm x 116 mm with a tolerance of + 15%
<b>Platen thickness</b>	4.5 mm with a tolerance of +2 mm
<b>Minimum fitting rod diameter (without the presence of lumps, grains and imperfections)</b>	12.7 mm $\pm$ 5%
<b>Fitting rod length</b>	268 mm $\pm$ 15%
<b>Round rod diameter of turnbuckles (without the presence of lumps, grains and imperfections)</b>	11 mm $\pm$ 5% tolerance, with ears for fastening
<b>Turnbuckles length</b>	330 mm $\pm$ 10% of length
<b>Minimum internal diameter for clamping ear</b>	20 mm
<b>Fitting material</b>	ASTM A-36 Steel Structure
<b>Yield point</b>	250 Mpa
<b>Minimum tensile strength</b>	400 Mpa
<b>Elongation in 50 mm minimum</b>	21%
<b>Galvanizing method</b>	ASTM A 123

## Applications:

- FTTH access network
- Telecommunication Networks
- CATV Networks
- Data communications Networks
- Local Area Networks