


DCSSF-STXXW-72CN

All-dielectric flat drop cable



1. Structure Diagram



2. The properties of single mode fiber (ITU-T G .657A2)

Items	Description	
	Before cable	After cable
atten.1310	$\leq 0.35\text{dB/km}$	$\leq 0.36\text{dB/km}$
atten.1383	$\leq 0.35\text{dB/km}$	$\leq 0.36\text{dB/km}$
atten.1550	$\leq 0.21\text{dB/km}$	$\leq 0.22\text{dB/km}$
atten.1625	$\leq 0.23\text{dB/km}$	$\leq 0.24\text{dB/km}$
Cable cut-off wavelength	$\leq 1260\text{ nm}$	
Zero-dispersion wavelength	1300 ~ 1324 nm	
Zero-dispersion slope	$\leq 0.091\text{ ps}/(\text{nm}^2.\text{km})$	
Mode field diameter	@ 1310 nm 8.8~9.6 μm	
Core/Clad concentricity error	$\leq 0.6\mu\text{m}$	
Cladding diameter	125 \pm 1.0 μm	
Cladding non-circularity	$\leq 1.0\%$	
Primary Coating diameter	245 \pm 7 μm	
Macro-bend induced attenuation 15 mm radius, 1 turn. 20mm radius, 1 turn. 30mm radius, 10 turns	$\Delta \leq 0.05\text{dB}$ $\Delta \leq 0.1\text{dB}$ $\Delta \leq 0.03\text{ dB}$	@1550nm @1550nm @1625nm

DCSSF-STXXW-72CN

All-dielectric flat drop cable



3. Cable Dimensions and Constructions

Items		Descriptions
Fiber	Fiber type	G657A2
	Original of the Optical Fiber	Certified Japanese Optical Fiber
	Fiber count	From 02 to 12 Cores
	Color	Blue/ Orange/ Green/ Brown/ Gray/ White/ Red/ Black/ Yellow/ Purple/ Pink/ Aqua
Loose tube	Material	PBT
	Diameter	3.0mm
	Water-blocking material	Gel-filled
Water blocking	Material	Water Blocking Yarn
	Quantity	2000D*4pcs
	Test	3meters sample, 24 hours no water leakage
Strength member	Material	FRP
	Diameter	1.8mm *2
Outer jacket	Material	HDPE (Nordic chemical new)
	Color	Black
	Thickness	0.9mm ± 0.05mm
	Cable height	4.7mm ± 0.1mm
	Width	8.3mm ± 0.1mm

4. Mechanical and Environmental Characteristics

Items	Descriptions	
Tensile Strength (IEC 60794-1-2 E1)	short-term	2000N
	long-term	1200N
Crush (IEC 60794-1-2 E3)	short-term	3000N/100mm
	long-term	1000N/100mm
Temperature Range (IEC 60794-1-2 F1)	Storage/Operation	-40°C-+70°C
	Installation	-10°C-+50°C
Bending Radius	Static	10D
	Dynamic	20D

5. Packing: Wooden Drums Protection

The cables are packed in plywood drum or fumigated wooden drum.

6. Delivery Length

Standard delivery length is per customer's requirements.