

OFP-7702AIW2

Fiber Optic Faceplate ABS Plastic for 2 Ports Simplex
SC Port or 02 Duplex LC Port, ABS Plastic (White)



Fiber Optic Faceplate (Wall Socket) — Indoor termination outlet for end-user FTTH/FTTx applications. Molded from high-quality ABS for durability and a clean finish. Provides a tidy handoff between building cabling and subscriber equipment.

Features

- Supports 2 × SC simplex (single mode) connections
- 2 SC simplex adapter ports (accepts standard SC simplex adapters)
- Mini rotary splice tray for up to 4 fiber splices (ideal for terminations and pass-through/maintenance loops)
- Material: High-quality ABS plastic
- Color: White
- Mounting: Wall-mounted or desktop use (as applicable to supplied accessories)

Typical applications

- FTTH/FTTx subscriber outlet, ONT handoff point, MDU/office drops

Name	Specifications	Qty
Fiber optic heat shrinkable protection sleeve	45mm*3.0*1.5	As per using capacity
Cable Tie Wrap	3mm*80mm white	3pcs
Plastic expansion pipe	Φ6mm white	2pcs
Screws	C type 4*25	2pcs

OFP-7702AIW2



Fiber Optic Faceplate ABS Plastic for 2 Ports Simplex
SC Port or 02 Duplex LC Port, ABS Plastic (White)

Dimension	Material	Adapter port	Capacity	Application
83.29x105x24.5mm	ABS plastic	2 ports	4 fibers	Indoor wall mounted

Applications:

- FTTH access network
- Telecommunication Networks
- CATV Networks
- Data communications Networks
- Local Area Networks

1-Fiber optic cable 2-Pigtail 3-Adapter 4-Pass the cable into the splice tray
5-Splice tray 6-Splice sleeve

