

# OFP-7704AIW2

Fiber Optic Faceplate ABS Plastic for 4 Ports Simplex  
SC Port, ABS Plastic (White)



## Fiber Optic Faceplate (Wall Socket) — 4 SC Ports

Indoor termination outlet for end-user FTTH/FTTx applications, molded from high-quality ABS in a clean white finish. The compact design provides a neat handoff between building cabling and subscriber equipment. It accepts **up to 4 SC simplex adapters** and includes a **mini rotary splice tray for up to 4 fiber splices**. Suitable for **wall-mounted or desktop** installation.

### Features

- Material: **ABS plastic**
- Color: **White**
- Adapter capacity: **4 × SC simplex adapters** (up to **4 fibers**)
- **Mini rotary splice tray for 4 splices**
- Wall-mounted or desktop application; quick, tidy installation

### Typical applications

- FTTH/FTTx subscriber outlet, ONT handoff point, MDU/office drops

Name	Specifications	Qty
Fiber optic heat shrinkable protection sleeve	40mm*3.0*1.5	4pcs
Cable tie	3mm*120mm white	5pcs
Plastic expansion pipe	Φ6mm white	2pcs
Screws	C type 4*25	2pcs

# OFP-7704AIW2

Fiber Optic Faceplate ABS Plastic for 4 Ports Simplex  
SC Port, ABS Plastic (White)



Dimension	Material	Adapter port	Capacity	Application
85x100x29mm	ABS plastic	4 ports	4 fibers	Indoor wall mounted

1. Fiber Optic Cable
2. Connector
3. Adapter

4. Pass the cable into the splice tray

5. Splice Tray
6. Splice Sleeve

