OSCV-48C

Fiber Optic Vertical Splice Closure (Black)









OSCV-48C Dome-Type Fiber Optic Closure — Built from high-quality engineering plastic for excellent strength and outdoor durability. The enclosure offers ample internal space for splicing, splitter integration, fiber storage, and organized routing/management, delivering a neat and reliable distribution point with waterproof performance. Versatile mounting options make it suitable for aerial spans, pole/wall installations (hardware included), and underground environments.


Features:

| Specifications | |
|-----------------------|---|
| Material: | ABS, anti UV |
| Size | 288*178 mm |
| Net Weight | 1.5 Kgs |
| Splice Trays: | 4 PCs, each with 12 cores |
| Splice Tray Dimension | 110*93*10 mm |
| Cable ports | 4 x 18mm |
| Seal | All ports are mechanically sealed |
| IP Rating | IP68 |
| Mounting | Aerial hanger, pole mounting, underground |

^{*}Pole Mounting accessories are optional

Installation:


Aerial Mounting (Included):



OSCV-48C

Fiber Optic Vertical Splice Closure (Black)





- 1- Fiber Optical Splice Closure
- 2- Hanger
- 3- Steel Wire
 - 1- Fixed Plate
- 2- Mounting Plate
- 3- U-Bolt
- 4- Telephone Pole

Pole Mounting:



Applications:

- FTTH access network
- · Telecommunication Networks
- CATV Networks
- Data communications Networks
- Local Area Networks

^{*}Pole Mounting accessories is included.